


► TENDER

	AX 1	AX 2	AX2AERO	AX3	AX 3AERO
DimENsiONs (mETERs - fEET/iNchEs)					
Overall length	2,0- 6'7"	2,4- 7'11"	2,4- 7'11"	2,6- 8'6"	2,6- 8'6"
Inside length	1,17- 3'10"	1,47- 4'10"	1,47- 4'10"	1,69- 5'7"	1,69- 5'7"
Overall width	1,15- 3'9"	1,15- 3'9"	1,15- 3'9"	1,42- 4'8"	1,42- 4'8"
Inside width	0,51- 1'8"	0,51- 1'8"	0,51- 1'8"	0,7- 2'4"	0,7- 2'4"
Buoyancy tube diameter	0,32- 1'1"	0,32- 1'1"	0,32- 1'1"	0,36- 1'2"	0,36- 1'2"
cApAcitY					
Passengers (ISO)	1+1	3	2	3	2+1
Maximum payload (kg - lbs)	170- 374,8	200- 440,9	240- 529,1	300- 661,4	300- 661,4
Total weight ¹ (kg - lbs)	20- 44	22- 48,5	22- 48,5	29- 63,9	32- 70,5
Airtight compartments	2	2	2+1	2	2+1+1
DEsigN cATEgORy²					
European directive N° 94/25/CE	-	-	-	D	D
mOTORisATIOn					
Shaft: ● Short ■ long ✖ Extralong * Ultralong ▲ Jet	●	●	●	●	●
Average recommended power (in HP)	2	2	2	3	3
Average recommended power (in kW)	1,5	1,5	1,5	2,3	2,3
Maximum power allowed (Hp)	3	3	3	4	4
Maximum power allowed (kW)	2,3	2,3	2,3	3	3
Maximum weight of outboard ³ (kg - lbs)	18- 39,7	18- 39,7	18- 39,7	26- 57,3	26- 57,3
Maximum speed (km/h - mph)	8- 5	8- 5	10- 6	10- 6	15- 9
hul l sTORAgE DimENsiONs (mETERs - fEET/iNchEs)					
Length	-	-	-	-	-
Width	-	-	-	-	-
Height	-	-	-	-	-
Length of the bag	0,85- 2'9"	0,9- 2'11"	0,94- 3'1"	1,03- 3'5"	1,1- 3'7"
Width of the bag	0,47- 1'7"	0,5- 1'8"	0,5- 1'8"	0,65- 2'2"	0,6- 1'12"
Height of the bag	0,3- 0'12"	0,3- 0'12"	0,3- 0'12"	0,3- 0'12"	0,32- 1'1"
Hull angle	-	-	-	-	-

(1) The weights indicated for the Typhoon, AX, MAX, AX Compact and MAX RIB include the floorboard, paddles/oars and pump.

(2) Applies only for EEC (European directive 94/25/CE).

(3) Maximum authorized weight: Dry weight, according to the engine manufacturers catalogue's specifications.

Equipment list

hull	Buoyancy Tube	STANDARD Equipment	main Optional Accessories
<ul style="list-style-type: none"> • Slatted floor (AX 1 / AX 2 / AX 3) • Removable Aerotec inflatable floor (AX 2 / AX 3) • Inflatable keel (AX 3) • Transom with aluminum engine support plate • 1 self-bailer 	<ul style="list-style-type: none"> • 1100Decitex fabric • Semi-recessed inflation valves (Bravo type) • Lifeline • Outlined profile rubbing strake • 1 bow handle • 2 towing rings • 2 reclining oar supports • 2 integrated hand pumps • Reinforced cone ends 	<ul style="list-style-type: none"> • 2 reinforced aluminum oars • 1 carry bag • 1 foot pump • 1 repair kit • Owner's manual 	<ul style="list-style-type: none"> • Lifting sling • Towing bridle • Inflatable thwart seat • Overall cover (AX 3) • Trim Tabs • Launching wheels • Electric pump

EquipMENT l iST

hul l	BuOyANcy TuBE	STANDARD EquipMENT	MAiN OpTiONAI AccESSORIES
<ul style="list-style-type: none"> • Slatted floor (MAX 1 / MAX 2 / MAX 3+) • Aerotec inflatable floor (MAX 2 / MAX 3+) • Marine plywood floor (MAX 3+ S) • Inflatable keel (MAX 2 AERO / MAX 3+ S / MAX 3+ AERO) • Transom with aluminum engine support plate • 1 self-bailer 	<ul style="list-style-type: none"> • 1100 Decitex fabric • Semi-recessed inflation valves (Bravo type) • 2 carrying handles • Lifeline • Outlined profile rubbing strake • 1 bowhandle • 2 towing rings • 2 reclining oar supports • Reinforced cone ends 	<ul style="list-style-type: none"> • Wooden bench • 2 reinforced aluminum oars • 1 fuel tank security strap (AERO models only) • 1 carry bag • 1 foot pump • 1 repair kit • Owner's manual 	<ul style="list-style-type: none"> • Kit faps • Bench bag • Removable bowbag hold-all • Lifting sling • Towing bridle • Overall cover (MAX 3+) • Launching wheels • Electric Pump