



► INFLATABLES

	C3	C4	C5
DIMENSIONS (METERS - FEET/INCHES)			
Overall length	3,8 - 12'6"	4,3 - 14'1"	4,7 - 15,5
Inside length	2,5 - 8'2"	3 - 9'10"	3,2 - 10'6"
Overall width	1,75 - 5'9"	1,75 - 5'9"	1,9 - 6'3"
Inside width	0,84 - 2'9"	0,84 - 2'9"	0,9 - 2'11"
Buoyancy tube diameter	0,455 - 1'6"	0,455 - 1'6"	0,5 - 1'8
CAPACITY			
Passengers (ISO)	6	7	9
Maximum payload (kg - lbs)	750 - 1653,5	870 - 1918,0	1150 - 2535,3
Total weight ¹ (kg - lbs)	98 - 216,1	109 - 240,3	128 - 282,2
Airtight compartments	3	3	4
DESIGN CATEGORY²			
European directive N° 94/25/CE	C	C	C
MOTORISATION			
Shaft: ● Short ■ long ✖ Extralong * Ultralong ▲ Jet	●	●	■
Average recommended power (in HP)	25	30	40
Average recommended power (in kW)	19	23	30
Maximum power allowed (Hp)	40	50	60
Maximum power allowed (kW)	30	38	45
Maximum weight of outboard ³ (kg - lbs)	98 - 216,1	109 - 240,3	128 - 282,2
Maximum speed (km/h - mph)	56 - 35	59 - 37	60 - 37
DIMENSIONS OF THE FOLDED BOAT (METERS - FEET/INCHES)			
Length of 1st bag	1,15 - 3'9"	1,2 - 3'11"	1,3 - 4'3"
Width of 1st bag	0,55 - 1'10"	0,55 - 1'10"	0,54 - 1'9"
Height of 1st bag	0,3 - 0'12"	0,3 - 0'12"	0,32 - 1'1"
Length of 2nd bag	0,98 - 3'3"	0,98 - 3'3"	1,28 - 4'2"
Width of 2nd bag	0,55 - 1'10"	0,55 - 1'10"	0,66 - 2'2"
Height of 2nd bag	0,15 - 0'6"	0,15 - 0'6"	0,22 - 0'9"

[1] The weights indicated for the Typhoon, AX, MAX, AX Compact and MAX RIB include the floorboard, paddles/oars and pump.

[2] Applies only for EEC (European directive 94/25/CE).

[3] Maximum authorized weight: Dry weight, according to the engine manufacturers catalogue's specifications.

EQUIPMENT LIST

HULL	BUOYANCY TUBE	STANDARD EQUIPMENT	OPTIONAL EQUIPMENT
<ul style="list-style-type: none"> • Rigid keel in 3 sections • Aluminium floor boards with built-in track • Aluminium motor plate • Attachment points for launching wheels • 2 self-bailers 	<ul style="list-style-type: none"> • Double thread 1100 Decitex fabric • Semi-recessed valves • Lacing cuff and safety grab line with front attachment cuff • Spray deflecting large profile rubbing strake • 2 towing rings • 2 lifting rings • 4 carrying handles • 1 metal bow handle • Reinforced cone ends 	<ul style="list-style-type: none"> • Carry bags with utility pockets • Fittings for rigid foredeck • 2 paddles • 1 footpump • 1 repair kit • Owner's manual • 1 pressure gauge • Bombard pennant 	<ul style="list-style-type: none"> • Jockey console • Bench mounted mini console • Adjustable bench • "Luxury" double seat • Rigid foredeck • Overall cover • Launching wheels • Bimini Top (C4 and C5) • Fishing rod holders • Boarding ladder • Trolley • Crossbar steering kit